DIGITUS ® *Professional*

Advanced HD Network Fixed Dome Camera

DN-16069-1
4016032325888

High Resolution - For a crisp view of the smallest details

Feeling safe is priceless. For this reason you should never compromise on security. Do we not have enough worries these days? Hand a part over: This camera is ideal for reliable indoor monitoring. The H.264 video standard ensures smooth, crystal clear images at a lower network load compared to legacy technologies. Thanks to infrared lighting in the dark the camera automatically switches to night mode. The megapixel sensor is inspiring: superior image quality and highest definition show even the tiniest detail. Not only the hardware is convincing: With auto motion detection and supplied software your equipment is future-proof and you save a lot of time! Just focus on the essential instead of painstakingly going through the daily recordings! Video images are only generated in case of activity. Even automatic face recognition is possible!

- True Day and Night surveillance
- Large aperture lens (F1.5)
- Prime lens: f3.8mm
- Viewing Angle: 62.7° (diagonal)
- High resolution and best video performance
- Future Proof - Compatible to all ONVIF devices
- Enhanced motion detection and alarm notification functions
- Built-in 10 MB Memory for Video Storage
- Alarm and event notification by FTP and Email
- Powerful mobile surveillance supporting iPhone, Blackberry and WinCE devices
- Low-latency video streaming with H.264 compression format
- Built-in loudspeaker and microphone for two-way communication
- External alarm output and input
- LAN Speed: 10/100Base-TX Ethernet
- Supported Protocols: DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP, IGMP, QoS
- Frame Rate NTSC: 30, PAL: 25
- Number of Online Users: 10
- Security: Multiple user access levels with password protection
- Management by web browser or CMS software for up to 16 network cameras control simultaneously
- Image Sensor: 1/4" Sony HR image sensor
- Resolution: 1280x1024 pixel NTSC / PAL
- Min Illumination 0.1 Lux / F1.5, 0 Lux (LED ON)
- Shutter Speed: 1 / 2 sec to 1 / 10000 sec.
- IR effective distance up to 10 meters
- Operating temperature: 0°C - 40°C
- Power Source: Power over Ethernet, 802.3af
- Dimensions (mm): 130(D) x 90.5(H)
- Supports Eagle Eyes App

PACKAGE CONTENT

- IP-Camera
- Manual
- Software CD
- RJ45 Adapter Cable

SMART PHONE APP · FACE TRACKING · 2 WAY AUDIO · MOTION DETECTION · Onvif SUPPORT · H.264